

KBR:kbr 03/24/08 875224 303514.01
PATENTRECEIVED
CENTRAL FAX CENTERAttorney Reference Number 3382-64472-01
Application Number 10/622,378

MAR 24 2008

Claims

1. (Currently Amended) In a computer system, a method of ~~processing~~ decoding images in a sequence of video images, the method comprising:

receiving and decoding a code in a bit stream to determine ~~determining~~ a fraction for a current image in the sequence, wherein the fraction represents an estimated temporal distance position for the current image relative to an interval between a first reference image for the current image and a second reference image for the current image, and wherein the determination of the fraction is independent of actual temporal distance positions of the respective reference images; and

for motion compensation for a direct mode macroblock in the current image, processing the fraction along with a motion vector for a co-located macroblock in the first reference image, wherein the motion vector represents motion in the first reference image relative to [[a]] the second reference image for the current image, and wherein the processing the fraction along with the motion vector results in a representation of motion for the direct mode macroblock in the current image relative to the first reference image and relative to the second reference image.

2. (Currently Amended) The method of claim 1 wherein the fraction is represented by the code, and wherein the code comprises a variable length code in [[a]] the bit stream.

3. (Currently Amended) The method of claim 1 wherein the fraction is selected from a set of discrete values, wherein each of the values are is greater than zero and less than one so as to indicate the estimated temporal distance position within the interval.

4. (Original) The method of claim 1 wherein the fraction is selected from the group consisting of: 1/2, 1/3, 2/3, 1/4, 3/4, 1/5, 2/5, 3/5, 4/5, 1/6, 5/6, 1/7, 2/7, and 3/7.

5. (Currently Amended) The method of claim 1 wherein the estimated temporal distance position for the current image relative to the interval between the first reference image for the current image and the second reference image for the current image is not the true temporal distance position of the current image.

KBR:kbr 03/24/08 875224 303514.01
PATENT

Attorney Reference Number 3382-64472-01
Application Number 10/622,378

6. (Original) The method of claim 1 wherein the fraction is based on motion information for the sequence of video images.

7. (Original) The method of claim 1 wherein the fraction is based on a proximity of the current image to an end of the sequence of video images.

8.-9. (Canceled)

10. (Currently Amended) The method of claim 1 further comprising repeating the acts of claim 1 for each of plural bi-directionally predicted images in the sequence of video images.

11.-17. (Canceled)

18. (Currently Amended) In a computer system, a method of encoding images in a sequence of video images, the method comprising:

determining a fraction for a current image in the sequence, wherein the current image has a previous reference image and a future reference image, and wherein the fraction represents a temporal position for the current image relative to ~~its~~ the respective reference images;

selecting direct mode prediction for a current direct mode macroblock in the current image;

finding a motion vector for a co-located macroblock in the future reference image;

scaling the motion vector for the co-located macroblock using the fraction;

using results of the scaling in motion compensation for the current direct mode macroblock in the current image; and

outputting a code in a bit stream, wherein the code represents the fraction, and wherein the outputting the code facilitates determination of the fraction independent of actual temporal positions of the respective reference images during decoding.

19. (Original) The method of claim 18 wherein the fraction facilitates representation of variable velocity motion in the direct mode prediction.

KBR:klr 03/24/08 875224 303514.01
PATENT

Attorney Reference Number 3382-64472-01
Application Number 10/622,378

20. (Currently Amended) The method of claim 18 wherein the scaling the motion vector for the co-located macroblock comprises scaling ~~the~~ a vertical component and a horizontal component[[s]] of the motion vector for the co-located macroblock.

21. (Currently Amended) The method of claim 18 wherein the scaling the motion vector for the co-located macroblock comprises:

scaling the motion vector for the co-located macroblock by a factor of the fraction, to obtain an implied forward motion vector for the current direct mode macroblock; and

scaling the motion vector for the co-located macroblock by a factor of the fraction minus one, to obtain an implied backward motion vector for the current direct mode macroblock, wherein for the direct mode macroblock the motion compensation uses the implied forward motion vector and the implied backward motion vector.

22.-73. (Canceled)

74. (New) The method of claim 2 wherein the determination of the fraction comprises looking up the variable length code in a variable length code table to obtain a value for the fraction.

75. (New) The method of claim 74 wherein at least one entry in the variable length code table represents a frame type, and wherein the frame type is B/I-frame.

76. (New) The method of claim 1 wherein the processing the fraction along with the motion vector comprises scaling the motion vector for the co-located macroblock using the fraction.

77. (New) The method of claim 76 wherein the scaling the motion vector for the co-located macroblock comprises scaling a vertical component and a horizontal component of the motion vector for the co-located macroblock.

KBR:kbr 03/24/08 875224 303514.01
PATENT

Attorney Reference Number 3382-64472-01
Application Number 10/622,378

78. (New) The method of claim 76 wherein the scaling the motion vector for the co-located macroblock comprises:

scaling the motion vector for the co-located macroblock by a factor of the fraction, to obtain an implied forward motion vector for the direct mode macroblock; and

scaling the motion vector for the co-located macroblock by a factor of the fraction minus one, to obtain an implied backward motion vector for the direct mode macroblock.

79. (New) The method of claim 78 wherein the motion compensation comprises:

addressing a macroblock in the future reference image using the implied forward motion vector;

addressing a macroblock in the previous reference image using the implied backward motion vector; and

predicting the current macroblock using an average of the macroblock in the future reference image and the macroblock in the previous reference image.

80. (New) One or more computer-readable storage media having stored thereon computer-executable instructions for causing one or more computers to perform a method of decoding images in a sequence of video images, the method comprising:

receiving and decoding a code in a bit stream to determine a fraction for a current image in the sequence, wherein the fraction represents an estimated temporal distance position for the current image relative to an interval between a first reference image for the current image and a second reference image for the current image, and wherein the determination of the fraction is independent of actual temporal distance positions of the respective reference images; and

for motion compensation for a direct mode macroblock in the current image, processing the fraction along with a motion vector for a co-located macroblock in the first reference image, wherein the motion vector represents motion in the first reference image relative to the second reference image for the current image, and wherein the processing the fraction along with the motion vector results in a representation of motion for the direct mode macroblock in the current image relative to the first reference image and relative to the second reference image.

KBR:kbr 03/24/08 875224 303514.01
PATENT

Attorney Reference Number 3382-64472-01
Application Number 10/622,378

81. (New) The computer-readable storage media of claim 80 wherein the fraction is represented by the code, and wherein the code comprises a variable length code in the bit stream.

82. (New) The computer-readable storage media of claim 80 wherein the fraction is selected from a set of discrete values, wherein each of the values is greater than zero and less than one so as to indicate the estimated temporal distance position within the interval.

83. (New) The computer-readable storage media of claim 80 wherein the fraction is selected from the group consisting of: $1/2$, $1/3$, $2/3$, $1/4$, $3/4$, $1/5$, $2/5$, $3/5$, $4/5$, $1/6$, $5/6$, $1/7$, $2/7$, and $3/7$.

84. (New) The computer-readable storage media of claim 80 wherein the estimated temporal distance position for the current image relative to the interval between the first reference image for the current image and the second reference image for the current image is not the true temporal distance position of the current image.

85. (New) The computer-readable storage media of claim 80 wherein the fraction is based on motion information for the sequence of video images.

86. (New) The computer-readable storage media of claim 80 wherein the fraction is based on a proximity of the current image to an end of the sequence of video images.

87. (New) The computer-readable storage media of claim 80 wherein the determination of the fraction comprises looking up the code in a code table to obtain a value for the fraction.

88. (New) The computer-readable storage media of claim 87 wherein at least one entry in the code table represents a frame type, and wherein the frame type is B/I-frame.

89. (New) A method of encoding images in a sequence of video images, the method comprising:

KBR:kbr 03/24/08 875224 303514.01
PATENT

Attorney Reference Number 3382-64472-01
Application Number 10/622,378

determining a fraction for a current image in the sequence, wherein the fraction represents an estimated temporal distance position for the current image relative to an interval between a first reference image for the current image and a second reference image for the current image, and wherein the determination of the fraction is independent of actual temporal distance positions of the respective reference images;

for motion compensation for a direct mode macroblock in the current image, processing the fraction along with a motion vector for a co-located macroblock in the first reference image, wherein the motion vector represents motion in the first reference image relative to the second reference image for the current image, and wherein the processing the fraction along with the motion vector results in a representation of motion for the direct mode macroblock in the current image relative to the first reference image and relative to the second reference image; and outputting a code in a bit stream, wherein the code represents the fraction.

90. (New) The method of claim 89 wherein the code comprises a variable length code in the bit stream.

91. (New) The method of claim 89 wherein the fraction is selected from a set of discrete values, wherein each of the values is greater than zero and less than one so as to indicate the estimated temporal distance position within the interval.

92. (New) The method of claim 89 wherein the fraction is selected from the group consisting of: $1/2$, $1/3$, $2/3$, $1/4$, $3/4$, $1/5$, $2/5$, $3/5$, $4/5$, $1/6$, $5/6$, $1/7$, $2/7$, and $3/7$.

93. (New) The method of claim 89 wherein the estimated temporal distance position for the current image relative to the interval between the first reference image for the current image and the second reference image for the current image is not the true temporal distance position of the current image.

94. (New) The method of claim 89 wherein the fraction is based on motion information for the sequence of video images.

KBR:kbr 03/24/08 875224 303514.01
PATENT

Attorney Reference Number 3382-64472-01
Application Number 10/622,378

95. (New) The method of claim 89 wherein the fraction is based on a proximity of the current image to an end of the sequence of video images.

96. (New) The method of claim 89 wherein the determination of the fraction comprises looking up the code in a code table to obtain a value for the fraction.

97. (New) The method of claim 96 wherein at least one entry in the code table represents a frame type, and wherein the frame type is B/I-frame.

98. (New) The method of claim 89 wherein the determining the fraction comprises:
evaluating each of plural fractions to determine bit costs for encoding the current image using the respective fractions; and
selecting the fraction based on the evaluating.

99. (New) One or more computer-readable storage media having stored thereon computer-executable instructions for causing one or more computers to perform a method of encoding images in a sequence of video images, the method comprising:

determining a fraction for a current image in the sequence, wherein the fraction represents an estimated temporal distance position for the current image relative to an interval between a first reference image for the current image and a second reference image for the current image, and wherein the determination of the fraction is independent of actual temporal distance positions of the respective reference images;

for motion compensation for a direct mode macroblock in the current image, processing the fraction along with a motion vector for a co-located macroblock in the first reference image, wherein the motion vector represents motion in the first reference image relative to the second reference image for the current image, and wherein the processing the fraction along with the motion vector results in a representation of motion for the direct mode macroblock in the current image relative to the first reference image and relative to the second reference image; and

outputting a code in a bit stream, wherein the code represents the fraction.

KBR:kbr 03/24/08 875224 303514.01
PATENT

Attorney Reference Number 3382-64472-01
Application Number 10/622,378

100. (New) The computer-readable storage media of claim 99 wherein the code comprises a variable length code in the bit stream.

101. (New) The computer-readable storage media of claim 99 wherein the fraction is selected from a set of discrete values, wherein each of the values is greater than zero and less than one so as to indicate the estimated temporal distance position within the interval.

102. (New) The computer-readable storage media of claim 99 wherein the fraction is selected from the group consisting of: $1/2$, $1/3$, $2/3$, $1/4$, $3/4$, $1/5$, $2/5$, $3/5$, $4/5$, $1/6$, $5/6$, $1/7$, $2/7$, and $3/7$.

103. (New) The computer-readable storage media of claim 99 wherein the estimated temporal distance position for the current image relative to the interval between the first reference image for the current image and the second reference image for the current image is not the true temporal distance position of the current image.

104. (New) The computer-readable storage media of claim 99 wherein the fraction is based on motion information for the sequence of video images.

105. (New) The computer-readable storage media of claim 99 wherein the fraction is based on a proximity of the current image to an end of the sequence of video images.

106. (New) The computer-readable storage media of claim 99 wherein the determination of the fraction comprises looking up the code in a code table to obtain a value for the fraction.

107. (New) The computer-readable storage media of claim 106 wherein at least one entry in the code table represents a frame type, and wherein the frame type is B/I-frame.

108. (New) The computer-readable storage media of claim 99 wherein the determining the fraction comprises:

KBR:kh 03/24/08 875224 303514.01
PATENT

Attorney Reference Number 3382-64472-01
Application Number 10/622,378

evaluating each of plural fractions to determine bit costs for encoding the current image using the respective fractions; and
selecting the fraction based on the evaluating.

109. (New) One or more computer-readable storage media having stored thereon computer-executable instructions for causing one or more computers to perform a method of encoding images in a sequence of video images, the method comprising:

determining a fraction for a current image in the sequence, wherein the current image has a previous reference image and a future reference image, and wherein the fraction represents a temporal position for the current image relative to the respective reference images;

selecting direct mode prediction for a current direct mode macroblock in the current image;

finding a motion vector for a co-located macroblock in the future reference image;

scaling the motion vector for the co-located macroblock using the fraction;

using results of the scaling in motion compensation for the current direct mode macroblock in the current image; and

outputting a code in a bit stream, wherein the code represents the fraction, and wherein the outputting the code facilitates determination of the fraction independent of actual temporal positions of the respective reference images during decoding.

110. (New) The computer-readable storage media of claim 109 wherein the fraction facilitates representation of variable velocity motion in the direct mode prediction.

111. (New) The computer-readable storage media of claim 109 wherein the scaling the motion vector for the co-located macroblock comprises scaling a vertical component and a horizontal component of the motion vector for the co-located macroblock.

112. (New) The computer-readable storage media of claim 109 wherein the scaling the motion vector for the co-located macroblock comprises:

scaling the motion vector for the co-located macroblock by a factor of the fraction, to obtain an implied forward motion vector for the current direct mode macroblock; and

KBR:kbr 03/24/08 875224 303514.01
PATENT

Attorney Reference Number 3382-64472-01
Application Number 10/622,378

scaling the motion vector for the co-located macroblock by a factor of the fraction minus one, to obtain an implied backward motion vector for the current direct mode macroblock, wherein for the current direct mode macroblock the motion compensation uses the implied forward motion vector and the implied backward motion vector.